Belinea

[Belinea 10 17 25]

Low cost entry to the colourful world of 17 inch LC-displays

Housed in an elegant black and silver casing, the technical details of the latest generation Belinea 10 17 25 are also very attractive.

The fast 16 ms response time and the integrated speakers being especially attractive to multimedia users. Top of the range contrast and brightness levels ensure excellent picture quality and certificates such as TCO99 and TÜV Ergonomics are evidence of excellent display properties.

SilverBlackStyle



D-Sub connection for analogue graphics cards

Integrated speaker

Belinea 10 17 25 – A Design-Oriented Newcomer

- 17 inch (43.18 cm)
- analogue
- Sound, TN-Panel
- Viewing angle: 140° / 130°
- Response time rise / fall: 4 / 12 ms

Target Groups

- **Representative workstations**
- **Video applications**
- **User who are needing a large screen size**

10/2004 @ Erros and omissions exempt. Art. Nr. 111727

MAXDATA Computer GmbH & Co. KG • Elbestraße 12-16 • D-45768 Marl • www.maxdata.de

MAXDATA
REAL HARD WARE

Belinea 10 17 25 – Technical Data

Panel characteristics

Image size	17"
Viewable image size in inch / cm	17" / 43.18
Max. picture size (w x h) in mm	338 x 270
Physical resolution	1280 x 1024
Pixel pitch in mm	0.264 x 0.264
Active Matrix, TFT	•
Displayable colours (max.)	16.2 Mio (FRC)
Brightness in cd / qm	260
Contrast ratio	450:1
Viewing angle horizontal	140°
Viewing angle vertikal	130°
Coating	Anti Glare
Response time: rise / fall in ms	4 / 12
Panel technology	TN
Back Light	4 CCFLs

Electronic data

Horizontal frequency in kHz	31 - 80
Vertical frequency in Hz	56 - 75
Bandwidth in MHz	135
Input voltage 100-240V, 50-60Hz	•
Power consumption in Watt (On / Sleep)	40 / 3
Input signal (VGA-card) analog / digital	• / –
Output audio amplifier	2 x 1 Watt

Features

Factory / user defined modes	16 / 9
OSD	•
Integrated microphone	–
Integrated speaker	•
Power supply in the panel / in the stand / external	– / – / •
Tilt back / forth	20° / 5°
Swivel right / left	– / –
Colour	SilverBlackStyle

Controls

Brightness / contrast	• / •
H / V position	• / •
Automatic picture-adjustment / colour calibration	• / •
Temperatur	•
Fine adjustment horizontal (clock) / vertical (phase)	• / •
Display at lower resolutions: 1:1 / full screen	– / •
Zoom / frequency	– / •
Recall / video signal selection	• / –
OSD position / OSD language(s)	• / 7
Mute	•
Volume	•

Max. refresh rates in Hz with resolution

640 x 480	75
800 x 600	75
1024 x 768	75
1152 x 864	75
1280 x 1024	75

Approvals / Standards

Plug & Play, DDC1 / 2B	•
Power-Management:	
Energy Star / Energy Label	• / –
TCO99	•
TÜV GS / TÜV Ergonomie	• / •
DIN 29241 / ISO 9241-3, -7, -8 / ISO 13406-2	• / • / •
Compliant to mountings acc.to VESA standard	• (75 x 75 mm)
MAC compliant	•

Connections

15 pin. Mini-D-Sub	•
24-pin DVI-D	–
Headphone plug	–
Audio In	•

Accessories

User manual (languages)	10
Power cable	•
Video connect. 15 pin. Mini-D-Sub	•
Video connect. 24 pin. DVI-D	–
Microphone cable	–
Audio cable	•

Physical specification

Size (w x h x d) in mm	380 x 392 x 156
Net / gross weight in kg	4.5 / 6

Warranty

3 years incl. panel and backlight	•

Austria
MAXDATA Computer GmbH
Ignaz-Köck-Straße 9 • 1210 Wien

Benelux
MAXDATA Benelux B.V.
Bredaseweg 113-115 • 4872 LA Etten-Leur

España • Portugal
MAXDATA Iberia
Edificio Prisma • C/ Colquide, 6
28230 – Las Rozas (Madrid)

France
MAXDATA S.A.R.L.
1, rue de Gevaudan • SILIC 1726
91017 EVRY-LISSES

Germany
MAXDATA Computer GmbH & Co. KG
Elbestraße 12-16 • 45768 Marl

Italy
MAXDATA Italia S.r.l.
Strada 1 • Palazzo F1
I-20090 Milanofiori, Assago (MI)

Poland
MAXDATA Sp. z o.o.
Ursynów Business Park • Ul. Puławska 303
02-785 Warszawa

Switzerland
MAXDATA Computer AG
Haldenstrasse 5 • 6340 Baar

United Kingdom
MAXDATA UK Limited
The MAXDATA Centre • Downmill Road
Bracknell, Berkshire RG12 1QS

With compliments: